



## Insert Panel (INS)


A fixed unit that can be directly and permanently fitted to a primary window or door. Alternatively, this unit can be fitted with turnbuckle releases to enable removal for cleaning and maintenance.



Removable section with turnbutton



Fixed section



Hinged section

### Features

- Slim, unobtrusive aluminium profile
- Most economical secondary system in the range
- Quick and simple installation
- Improved noise and thermal installation
- Enhanced security
- Suitable for arched, shaped and bespoke applications
- Ideal for use where space is limited – i.e behind shutter

### Specification

- Glazing options: 4mm – 6.8mm
- 16mm x 24mm aluminium insert section – no timber subframe
- Pre-drilled for face fix only
- Woolpile inserted into panel section groove to create outer frame seal
- Gasket colour option of black or white
- Standard colour white high gloss – RAL 9910

### Variations of Basic Unit

- Removable using small lightweight turn buttons to create fixing around the perimeter (maximum 10kg weight)
- Side hung unit created with small lightweight plastic hinges and turn button to close (maximum 10kg weight)
- Subframe mounted using a 20mm x 21mm timber, which can be utilised with fixed, turn buttons or hinged option
- Variety of stock colours available, including all RAL options
- Can accept flyscreen mesh

#### Traditional

#### Configurations:

#### INS



Max width: 1,200mm  
 or Max height: 2,000mm